

HM 8 - 400 EM

hand-feed chipper

| | |
|-------------------|---|
| In-feed height: | 400 mm |
| In-feed width: | 670 mm |
| Transport height: | 2.492 mm |
| Transport width: | 2.843 mm |
| Ejection height: | 3.300 mm |
| Working width: | 3.817 mm |
| Total length: | 2.430 mm |
| Weight: | approx. 4.360 kg |
| Flywheel mass: | 470 kg |
| In-feed: | Conveyor belt length: 600 mm In-feed table length: 900 mm Pressure roller with steel teeth: Ø 450 mm |
| Sieve: | Standard mesh 35x40 mm |
| Chipping drum: | Ø 495 mm with quick change blades |
| Drive RPM: | max. 750 rpm |
| Electric motor: | Electric motor 55 kW / 1.500 rpm V-belt drive, control panel with star-triangle automatic start |
| | Electric motor 75 kW / 1.500 rpm V-belt drive, control panel with soft start |
| Flywheel: | Ø 1.370 mm, 90 mm wide |
| Ejection: | manuel foldable and rotatable (optional with electric drive), Support by pneumatic shock dampers |
| Control: | automatic load-dependent in-feed control with intergraded cycle mode, two day counters and one overall operating hours counter, in-feed speed infinitely adjustable, Connection by customer in accordance with DIN-VDE |

Energy in Balance with Nature

Tough • reliable • powerful • efficient