



technical specifications RHK-AK 475

width (mm)	890 (889)
length (mm)	1550
height (mm)	1645 (1643)
width with cover panel (mm)	1085
length with cover panel (mm)	1690
height with cover panel (mm)	1645
water content (l)	385
weight (kg)	1400
heating surface (m ²)	7,20
heating output (kW)	0-75
rated heat output (kW)	75
CO ² (%)	10,00
efficiency (%)	>90
flue gas mass flow (kg/Sek.)	0.067000
flue gas temperature (°C)	180
flue depress (Pa)	33
flue depress with fgb (Pa)	14
flue depress with underpressure control (Pa)	10
pressure drop at dT 10K (mbar)	15,20
max. pressure (bar)	3
heat flow (Zoll)	1 1/2
heat return (Zoll)	1 1/2
safety flow (Zoll)	1 1/2
safety return (Zoll)	1 1/2
filling and draining (Zoll)	3/4
safety cooling inlet (Zoll)	-
safety cooling outlet (Zoll)	-
safety sensor valve (Zoll)	-
flue gas pipe Ø (mm)	200
min. opening for air supply (cm ²)	200
power supply	400V/16A 5polig
min. volume flow rate for return flow boot at 15K (m ³ /h)	1,43

technical specifications RHK-AK 475

Stand 29.04.2011

Fa. Heizomat GmbH - Gerätebau / Energiesysteme - 97110 Gunzenhausen - OT Maicha 21 - 09836/9797-0

the right to any changes as
may be technically or legally
required is reserved.